

WITH AUTOFEED, COOLANT SYSTEM, PARTIALLY ROTATING TABLE,  
WITH 125MM VICE.



Max drilling capacity on cast iron with pre-drilling hole	Ø 31,75 mm
Max drilling capacity on steel with pre-drilling hole(s235jr)	Ø 31,75 mm
Continuous drilling capacity	Ø 25 mm
Spindle taper	MT 3
Chuck sizes	1 - 16 B18
Spindle speed	(8) 160 - 2200 rpm
Spindle travel	130 mm
Column	Ø 115 mm
Feed range	0,1- 0,16- 0,26 mm/giro
Distance between spindle axis and column	223 mm
Distance between spindle nose and table	696 mm
Distance between spindle nose and base	1135 mm
Table dimensions	400 x 470 mm
Travel of table	510 mm
Slot	14 mm
Base dimensions	400 x 310 mm
Motor	400 V 50 Hz 0,85 kW / 1,1 kW
Cooling pump	400 V 50 Hz 40 W
Overall sizes	900 x 545 x 1765 mm
Net weight	340 kg
Packaging dimensions	950 x 570 x 1920 h mm
Gross weight	360,50 kg
EAN Code	8012667226855

### Included

Drill chuck with key 1 - 16 B18  
Spindle drilled MT 3  
Reduction sleeve MT 3/2