ART. 0252/400V FLOOR DRILL PRESS WITH DRIVE BELT



NEW BELT TENSION DEVICE, REVERSIBLE TABLE WITH INTEGRATED SLIDING VICE, DRILLING DEPTH READOUT, LED LIGHT INCLUDED. ELECTRICAL...









Max drilling capacity on cast iron with pre-drilling hole

Max drilling capacity on steel with pre-drilling

hole(s235jr)

Continuous drilling capacity

Spindle taper

Chuck sizes

Spindle speed

opinale speed

Spindle travel

Quill

Column Height

Distance chuck-column

Distance between spindle nose and table

Distance between spindle nose and base

Table dimensions

Slot

Vice

Motor

Net weight

Packaging dimensions

Gross weight

EAN Code

Ø 32 mm

Ø 28 mm

Ø 20 mm

CM 4

1 - 16 mm B18

(12) 150 - 2450 rpm

120 mm

ø 62 mm

ø 92 mm

1720 mm

255 mm

700 mm

1220 mm

460 x 425 mm

14 mm

210 x 165 mm

400 V 50 Hz 1,5 kW

135 kg

1420x660x350 h mm

143,00 kg

8012667254230

Included

Keyless chuck 1 - 16 B18 Drill chuck shank MT 4

