

WITH ROTATION SELECTION AND DRIVE BELT.



Max drilling capacity on steel with pre-drilling hole(s235jr)	32 mm
Face milling cutter max	80 mm
End milling cutter max	20 mm
Spindle taper	CM 3
Chuck sizes	1 - 13 mm B16
Spindle speed	100 - 2080 rpm
Spindle travel	130 mm
Spindle rotation	Dx - Sx
Column	115 mm
Quill	75 mm
Headstock travel	405 mm
Manual vertical feed division	0,05 mm
Distance spindle axis - column surface	197 mm
Distance between spindle nose and table	600 mm
Table dimensions	585 x 190 mm
Slot	12 mm
Longitudinal axis	180 mm
Cross axis	380 mm
Base dimensions	470 x 670 mm
Motor	400 V 50 Hz 1,5 kW
Cooling pump	400v 50 Hz 0.4 KW
Dimensions	928 x 910 x 1700h mm
Net weight	300 kg

Included

Drill chuck with key 1 - 13 B16
Spindle drilled MT 3 B16
Spindle taper shank MT 3 Ø 27 mm
Reduction sleeve MT 3/2
Coolant system
Oilers
Tie rod M12
Service keys

Packaging dimensions	960x760x1870 h mm
Gross weight	310,00 kg
EAN Code	8012667309732