

ROTATING AND INCLINABLE TABLE. ELECTRICAL SYSTEM WITH SEPARATE 24V CIRCUIT FOR ON-BOARD MACHINE CONTROLS.



|                                                               |                     |
|---------------------------------------------------------------|---------------------|
| Max drilling capacity on cast iron with pre-drilling hole     | Ø 25 mm             |
| Max drilling capacity on steel with pre-drilling hole(s235jr) | Ø 20 mm             |
| Continuous drilling capacity                                  | Ø 16 mm             |
| Spindle taper                                                 | CM 3                |
| Chuck sizes                                                   | 1 - 16 mm B18       |
| Spindle speed                                                 | (16) 220 - 2840 rpm |
| Spindle travel                                                | 80 mm               |
| Quill                                                         | Ø 47 mm             |
| Column                                                        | Ø 80 mm             |
| Height                                                        | 980 mm              |
| Table dimensions                                              | 290 x 290 mm        |
| Distance spindle axis - column surface                        | 175 mm              |
| Distance between spindle nose and table                       | 420 mm              |
| Distance between spindle nose and base                        | 600 mm              |
| Slot                                                          | 14 mm               |
| Tilting table                                                 | ± 45°               |
| Turning table                                                 | Yes                 |
| Base dimensions                                               | 460 x 275 mm        |
| Motor                                                         | 230 V 50 Hz 0,75 kW |
| Dimensions                                                    | 300 x 630 x 990h mm |
| Net weight                                                    | 57 kg               |
| Packaging dimensions                                          | 890x560x330 h mm    |
| Gross weight                                                  | 60,00 kg            |

**Included**

Keyless chuck 1 - 16 B18  
Drill chuck shank MT 3

EAN Code

8012667346478