

REVERSIBLE, WITH AUTOMATIC FEEDING, COOLANT SYSTEM,
 EQUIPPED WITH LED LIGHT. WITH GEAR SPEED CHANGE.



Max drilling capacity on cast iron with pre-drilling hole	40 mm
Max drilling capacity on steel with pre-drilling hole(s235jr)	32 mm
Continuous drilling capacity	28 mm
Spindle taper	MT 4
Chuck sizes	3 - 16 mm B16
Spindle speed	(6) 75 - 1220 rpm
Spindle travel	220 mm
Quill	65 mm
Column	180 mm
Distance between spindle axis and column	350 - 870 mm
Distance between spindle nose and table	0 - 640 mm
Distance between spindle nose and base	310 - 980 mm
Feed range	(3) 0,1 - 0,16 - 0,25 mm/rev
Cube dimensions	550 x 390 x 350 mm
Slot	18 mm
Base dimensions	1300 x 650 mm
Motor	400 V 50 Hz 1,5 kW
Lifting motor radial arm	400V 50 Hz 0,55 kW
Cooling pump	400V 50 Hz 0,40 kW
Dimensions	1400 x 650 x 1900 h mm
Net weight	1050 kg
Packaging dimensions	1550x750x2100 h mm
EAN Code	8012667362133

Included

Drill chuck with key 3 - 16 mm B16
 Spindle drilled MT 4 B16
 Reduction sleeve MT 4/3
 LED Lamp
 Coolant system
 Base cube

Gross weight

1150,00 kg