

REVERSIBLE WITH COOLANT SYSTEM AND TEMPORISED TAPPING.



Max drilling capacity on cast iron with pre-drilling hole	Ø 40 mm
Max drilling capacity on steel with pre-drilling hole(s235jr)	Ø 32 mm
Face milling cutter max	Ø 80 mm
End milling capacity	Ø 25 mm
Tapping capacity	Ø 22 mm
Morse taper	MT 4
Spindle speed	(12) 75 - 3200 rpm
Spindle travel	130 mm
Spindle rotation	Dx - Sx
Quill	Ø 76 mm
Column	Ø 115 mm
Head tilt left and right	± 60°
Manual vertical feed division	0.02 mm
Distance spindle axis - column surface	260 mm
Distance between spindle nose and table	715 mm
Table dimensions	585 x 190 mm
Table slots	12 mm
Longitudinal axis	360 mm
Cross axis	250 mm
Base dimensions	648 x 412 mm
Base slot	14 mm
Motor	400 V 50 Hz 1,1 - 1,5 kW
Cooling pump	400 V 50 Hz 40 W

### Included

Self-locking chuck 1 - 16 mm B16  
 Drill chuck with key 1 - 13 mm B16  
 Drill chuck shank MT 4 B16  
 Spindle taper shank MT 4 Ø 27 mm  
 Reduction sleeve MT 4/3  
 Reduction sleeve MT 3/2  
 Oilers  
 Tie rod M16  
 Service keys  
 Coolant system

<b>Overall sizes</b>	740 x 790 x 1960h mm
<b>Net weight</b>	355 kg
<b>Packaging dimensions</b>	830x760x1870 h mm
<b>Gross weight</b>	381,50 kg
<b>EAN Code</b>	8012667199548