

WITH AUTOFEE, COOLANT SYSTEM, PARTIALLY ROTATING TABLE, WITH 125MM VICE.



€4.220,00







Max drilling capacity on cast iron with pre-drilling hole

Max drilling capacity on steel with pre-drilling

hole(s235jr)

Continuous drilling capacity

Spindle taper

Chuck sizes

Spindle speed

Spindle travel

Column

Feed range

Distance between spindle axis and column

Distance between spindle nose and table

Distance between spindle nose and base

Table dimensions

Travel of table

Slot

Base dimensions

Dase difficilisions

Motor

Cooling pump
Overall sizes

Net weight

Packaging dimensions

Gross weight

EAN Code

Ø 31,75 mm

Ø 31,75 mm

Ø 25 mm

MT3

1 - 16 B18

(8) 160 - 2200 rpm

130 mm

Ø 115 mm

0,1-0,16-0,26 mm/giro

223 mm

696 mm

1135 mm

400 x 470 mm

510 mm

14 mm

400 x 310 mm

400 V 50 Hz 0,85 kW / 1,1 kW

400 V 50 Hz 40 W

900 x 545 x 1765 mm

340 kg

950 x 570 x 1910 mm

360,50 kg

8012667226855

Included

Drill chuck with key 1 - 16 B18 Spindle drilled MT 3 Reduction sleeve MT 3/2

