

REVERSIBLE, WITH TAPPING FUNCTION, REVERSIBLE TABLE WITH 120MM VICE.



Max drilling capacity on cast iron with pre-drilling hole	Ø 30 mm
Max drilling capacity on steel with pre-drilling hole(s235jr)	Ø 28 mm
Continuous drilling capacity	Ø 25 mm
Spindle taper	3
Chuck sizes	1 - 16 mm B18
Spindle speed	(16) 127 - 2380 rpm
Spindle travel	100 mm
Quill	Ø 62 mm
Column	Ø 98 mm
Distance between spindle axis and column	203 mm
Distance between spindle nose and table	145-895 mm
Distance between spindle nose and base	1200 mm
Table dimensions	350 x 280 mm
Slot	12 mm
Tilting table	±90°
Vice	90 mm
Base dimensions	410 x 560 mm
Motor	400 V 50 Hz 0,5 / 1 kW
Dimensions	530 x 820 x 1700 mm
Net weight	200 kg
Packaging dimensions	570x790x1860 h mm
Gross weight	224,00 kg
EAN Code	8012667256197

Included

Drill chuck with key 1 - 13 mm B16
Drill chuck shank MT 3 B16
Morse taper reduction sleeve MT 3/2
Morse taper reduction sleeve MT 2/1