


SE UTILIZA PRINCIPALMENTE EN TORNOS CON EL OBJETIVO DE ESTABILIZAR PIEZAS LARGAS Y DELGADAS, MÁS SUJETAS A FLEXIONES U...



€309,00



Cono mordazas

A	4
B	L2 61,5 mm - D2-D3 28 mm - $\hat{I} \pm 60^\circ$ mm
C	L2 55,5 mm - D2-D3 28 mm - $\hat{I} \pm 75^\circ$ mm
D	L2 51,5 mm - D2-D3 28 mm - $\hat{I} \pm 90^\circ$ mm
E	L2 69 mm - D2-D3 26 mm - $\hat{I} \pm 60^\circ$ mm
F	L2 61,5 mm - D2-D3 50 mm / 28 mm - $\hat{I} \pm 60^\circ$ mm
G	L2 55 mm - D2-D3 40 mm / 35 mm - $\hat{I} \pm 60^\circ$ mm
	L2 60 mm - D2-D3 55 mm / 48 mm - $\hat{I} \pm 60^\circ$ mm

Máx. r.p.m.

5000 g/min

Capacidad máx.

240 kg

Peso bruto

3,88 kg

Dimensiones de embalaje

380x225x110 h mm

Codigo de barras

8012667011178



Estuche de transporte



Templado



9 Pcs



Acero



Rectificado