



<b>Max drilling capacity on cast iron with pre-drilling hole</b>	Ø 28 mm
<b>Max drilling capacity on steel with pre-drilling hole(s235jr)</b>	Ø 25 mm
<b>Continuous drilling capacity</b>	Ø 20 mm
<b>Column</b>	Ø 85 mm
<b>Spindle travel</b>	93 mm
<b>Distance between spindle axis and column</b>	180 mm
<b>Max distance spindle nose - table</b>	360 mm
<b>Max distance spindle nose - base</b>	595 mm
<b>Spindle taper</b>	3
<b>Spindle speed</b>	(9) 240 - 2710 rpm
<b>Working area of the table</b>	255 x 215 mm
<b>Table dimensions</b>	310 X 280 mm
<b>Slot</b>	14 mm
<b>Working area of the base</b>	245 x 250 mm
<b>Travel of table</b>	265 mm
<b>Three-phase motor</b>	400V 50Hz 1,1 kW
<b>Overall sizes</b>	730 x 440 x 1060 mm
<b>Packaging dimensions</b>	780x560x1200 h mm
<b>Gross weight</b>	118,00 kg
<b>EAN Code</b>	8012667283957

## Included

1 - 13 mm chuck B 18  
Chuck shank CM 3 B 18  
Reduction sleeve CM 3/2